



## **PRODUCT SPECIFICATION – “SLG200” - SLIDING GATE**

### **PROPRIETARY SPECIFICATION**

“SLG200” sliding gate as manufactured by Gryffin High Security Fencing and Gates

#### **SUB FRAME**

Gate structure shall be manufactured using pre-galvanised steel SHS / RHS sections

#### **GATE INFILL**

Infill shall be typically vertical bar utilising 25mm SHS.

#### **GATE SUPPORT**

Support for Leaf shall be way of manufactured pre-galvanised steel SHS Tunnel Posts. They can be affixed to concrete structures by bolted connection or encased within Infill shall be typically vertical bar utilising 25mm SHS.

#### **AUTOMATION**

Automation is provided via high duty electro-mechanical gate operator.

Gryffin safety supplied as standard with in built obstacle detection, dual height and dual side photo-electrical beams, flashing light and warning sign.

#### **FINISH OPTIONS**

- Galvabond steel (standard)
- Dulux Duralloy or Interpon D100 powdercoat finish
- Electro – static twin coat wet sprayed paint.

#### **SPECIAL NOTES:**

- The power supply required for the motor is either:
  - Single phase hard wired (10 amp), located within one metre of the motor.
  - Low voltage 24v wired supply, within one metre of the motor.
  - 24v High efficiency solar power.

Gryffin High Security Fencing and Gates has continuous program of product development, and reserve the right to change specifications at any time without notice