



GRYFFIN
HIGH SECURITY FENCING & GATES
Smarter solutions, guaranteed.

SWING GATE

SWG Series





SWING GATE SYSTEMS

Gryffin High Security Fencing and Gates is proud to be serving industry since 1984. For over forty years the company has been manufacturing Swing Gates for commercial and industrial use, setting the pace with innovative design and proven product excellence.

Gryffin manufactures a comprehensive range of Swing Gates for all commercial and industrial applications including;

- Factories
- Warehouses
- Distribution Centres
- Carpark Entrances
- Loading Docks
- Sporting Complexes
- Local and State Government Projects
- Schools and other Education facilities

We use computer aided design programs extensively in our research and development process seeking to improve the strength and efficiency in our product offering.

We make to measure to ensure correct fit and that installation on site is completed quickly and efficiently.

Don't hesitate to contact Gryffin to discuss your specific application requirements.

SPECIFICATIONS

Sub Frame

Gate structure is manufactured from pre-galvanised steel SHS/RHS sections.

Material thickness is dependent on the opening width and the security requirements of the project.

Size

Refer to the table below.

Height of gate to suit fence line: standard heights 1,800mm – 2,400mm, higher if required.

Gate Infill

Infill typically vertical bar utilising 25mm SHS. A range of other options are available including palisade, RHS, angles, bar configuration, weld mesh, cladding or a bespoke finish to suit specific site requirements.

Automation

Automation is provided via high duty electro-mechanical gate operator.

Safety supplied as standard with in built obstacle detection, dual height and dual side photo-electrical beams, flashing light and warning sign.

A range of control options are available including access control, radio control or Vehicle detection loop system.

Comparison

	SWG100	SWG200	SWG300
Max Width Single Leaf Gates	3,000mm	6,000mm	10,000mm
Max Width Double Gates	6,000mm	12,000mm	20,000mm

Get in touch today to discuss your specific requirements.

Finish Options

- Galvabond steel (standard).
- Dulux Duralloy or Interpon D1000 powdercoat finishes are suitable.
- Electro-static twin coat wet sprayed paint.

Special Notes

- The power supply required for the motor is either:
 - Single phase hard wired (10 amp), located within one metre of the motor.
 - Low voltage 24v wired supply, within one metre of the motor.
 - 24v High efficiency solar power.
- Work by others:
 - Power supply provision if required.
 - Structurally adequate footings / mounting points to support the gate.
- Product warranty – 12 months.



Phone: 1800 672 066 (Australia Wide) | **Website:** www.gryffin.com.au



Victoria

8 Bessemer Road,
Bayswater North VIC 3153

sales@gryffin.com.au

New South Wales

138 Fairey Road,
South Windsor NSW 2756

nswsales@gryffin.com.au