GRYFFIN
HIGH SECURITY FENCING & GATES
Smarter solutions, guaranteed.

PRODUCT SPECIFICATION – LONG BARB TIGERTAPE™

PROPRIETARY SPECIFICATION

LONG BARB TIGERTAPE™ as manufactured by Gryffin High Security Fencing and Gates

Stainless Steel Tape

- 301 grade Austenitic 0.5mm thick(+/-0.06)
- 3/4 hard to HV370 (+/-20min).
- Tensile Strength: 1158 MPA(min).
- Yield Strength: 760 MPA(min).
- Australian standard AS 1449 301.

Tape Configuration

- Clusters of Barbs at 100mm centres.
- Each barb 60mm (approx) long with needle sharp points.

Recommended Spacing

Each clipped pair is tied at 300m centres giving an effective density of one loop per 150mm.

Hard-Drawn Galvanized Spring Steel Wire Range 2

- Standard: AS 1472/1979 • Diameter: 2.5mm (+/-0.02)
- Tensile Strength: 1730-1950 MPa
- Galvanizing: Galvanized 125g/m2 (min)
- Class WO5 AS4534-1998.

Concertina Clips

1.5mm thick x 10mm wide 304 grade stainless steel.

Fully clenched, interlocking tongue.

Gryffin High Security Fencing and Gates has continuous program of product development, and reserve the right to change specifications at any time without notice