



PRODUCT SPECIFICATION – SHORT BARB TIGERTAPE™

PROPRIETARY SPECIFICATION

SHORT BARB TIGERTAPE™ as manufactured by Gryffin High Security Fencing and Gates

Galvanized Blade Strip

- Galvabond G2 0.55mm Thick
- Coating Class Z275
- Hardness HR30T 50-60 (typical)
- Surface Finish: Spangled
- Surface Treatment: Chromated
- Australian Standard AS 1397

Tape Configuration

- Clusters of barbs at 25mm(+/-1mm) centres
- Each barb 10mm (approx) long with needle sharp points.
- Width of barbed tape: 14mm. Hard-Drawn Galvanized Spring Steel Wire Range 2
- Standard: AS 1472/1979 • Diameter: 2.5mm (+/-0.02)
- Tensile Strength: 1730-1950 MPa
- Galvanizing: Galvanized 125g/m² (min)
- Class WO5 AS4534-1998.

Concertina Clips

- Galvabond G2 1.6mm Thick x 9.7mm wide
- Coating Class Z275
- Hardness HR30T 50-60 (typical)
- Surface Finish: Spangled
- Surface Treatment: Chromated
- Australian Standard AS 1397

Gryffin High Security Fencing and Gates has continuous program of product development, and reserve the right to change specifications at any time without notice